

LED side light inground light



Stainless steel front cover




A1E2WC0116A



A2E2WC0116A



A4E2WC0116A



Specifications

Housing	12' Die-casting grey powder coated aluminum(RAL432U) T=60-80um,Adhesion of ISO class 1/ASTM class 4B Adhesion of ISO class 1/ASTM class 4B
Front cover	Stainless steel SUS 316'
Loading capacity	> 2000kg
Cable gland	Molding shaped silicone seat
Operating temperature	-20°C~40°C
Mounting sleeve	011 ABS plastic
Power cable	24VDC low voltage: H05RN-F 2X1.0mm ² L=0.5m (low voltage) Main voltage: H05RN-F 3X1.0mm ² L=0.5m (high voltage)

Item No.	Light source	The manufacturer selected lens	Degree (°)	Input voltage (v)	Typical operating current(mA)	Typical consumption(w)	Typical luminance (lm)	IK rate
A1E2WC0116A	1×2W	B4	30	24VDC 120/240	24V=110 120V=48 240V=31	24V=2.6 120V=3.3 240V=3.6	Cool white=1.5 Warm white=1.3	10
A2E2WC0116A	1×2W	B4	30	24VDC 120/240	24V=110 120V=48 240V=31	24V=2.6 120V=3.3 240V=3.6	Cool white=2 Warm white=1.7	10
A4E2WC0116A	1×2W	B4	30	24VDC 120/240	24V=110 120V=48 240V=31	24V=2.6 120V=3.3 240V=3.6	Cool white=2 Warm white=1.7	10