






# Slim style high power LED wall washer



## Low voltage power



Installed on the ground



Installed on the wall



## Specifications

Housing	Extruded aluminum, powder coated
Bracket	Stainless steel SUS 316* T=1.5mm
Glass	Tempered glass, T=3mm
Lens	Optical lens, efficiency ≥ 85%
Cable gland	PVC IP-69 PO-9
Casket	Glass and housing are silicone sealed
LED	Single color 3030 SMD power LED
	Multi color TO power LED
Operating temperature	-20°C ~ 40°C
Power cable	<b>120/240V:</b> H05RN-F 3 × 1.0mm <sup>2</sup> L=0.5M <b>RGB 24VDC:</b> H05RN-F 5 × 0.75mm <sup>2</sup> L=0.5M

Item No.	Light source	The manufacturer selected lens	Degree (°)	Length L (mm)	Input voltage (v)	Typical operating current (mA)	Typical consumption (w)	Typical luminance (lm)	IK rate
AB6R1256A	12 × 1W Single color	B27	25	500	120/240	120=130 240=65	15	Cool white=880 Warm white=665	02
AB6R1205A	12 × 1.5W RGB 3in1	B21	35	500	24VDC	R=275 G=302 B=303	12	363	02
AB6R2456A	24 × 1W Single color	B27	25	1000	120/240	120=260 240=130	28	Cool white=1760 Warm white=1642	02
AB6R2405A	24 × 1.5W RGB 3in1	B21	35	1000	24VDC	R=537 G=606 B=602	42	763	02